



ArtNo:	4410-0350-1080-2120
Height:	21mm
Width:	30mm
Length:	360mm
Screw-on:	Yes
Number of poles:	8
Plug contact:	Yes
Channels:	2
Material:	PVC
At CC:	350mA
Weight:	213g
Power consumption:	80W
Power supply:	AC - 230V
Surface and color:	white
IP Schutzart:	IP20

10 YEARS WARRANTY
PRODUCED IN ITALY

- DA 2
- DA 1
- PUSH L
- L
- N

FW: 1.11
PATENTED
170001396411
MADE IN ITALY
T-LED 80/350 DALI SLIM 1%
Dimmable AC/DC P/S for LED
cod. 127091

PRI: 220 - 240 V 0/50-60 Hz
I_{max}=0,4 A; λ (P>35W)=0,95
SEC: 140-350mA; U_{out}=300V;
*V_{omin}=30V
FRI
I_a= -25...50°C; t_c=85°C
176-276Vdc range x emerg. appl.; I_{max}=0,5A
U_{out}=300V ---

SEC	Vomax	Pomax	1	2	3	4	SEC	Vomax	Pomax	1	2	3	4
140 mA	250V	3,5 W	-	-	-	-	260 mA	250V	6,5 W	ON	-	-	-
145 mA	250V	3,8 W	-	-	-	-	275 mA	250V	68,5 W	ON	-	-	-
170 mA	250V	42,5 W	-	-	-	-	290 mA	250V	72,5 W	ON	-	-	-
185 mA	250V	46 W	-	-	-	-	305 mA	250V	76 W	ON	-	-	-
200 mA	250V	50 W	-	-	-	-	320 mA	250V	80 W	ON	-	-	-
215 mA	250V	53,5 W	-	-	-	-	335 mA	235V	80 W	ON	-	-	-
230 mA	250V	57,5 W	-	-	-	-	350 mA	228V	80 W	ON	-	-	-
245 mA	250V	61 W	ON	-	-	-				ON	-	-	-

Before use, always check SW1 dipswitch settings

DALI
 CE
 EMC
 KEMA
 EL
 KEMA
 DALI
 DALI

242220-01
 300mA-12
 t_c
 0,2 - 1,5
 0,5 - 8,5mm
 JPEL 3000
 GMA-506106
 K2903

ON
 00000
 SEC 1 2 3 4
 NTC
 SEC +